

## Wadsworth thermostats are commercial-grade controls built to survive in wet and harsh environments



**Part #E-1613**

Shipping Wt. 2 lb | .9 kg



### Two-Stage Thermostat Features:

- Two stages for heating or cooling
- Two SPDT staged switches for heating or cooling
- Rugged, weather resistant enclosure
- Corrosion-resistant materials for long life
- Low mass, high surface area of stainless steel coiled sensor provides rapid response to temperature change
- Temperature Range: 40° to 110° F (4° to 43° C)
- UL Listed, CSA Certified
- NEMA 4X enclosure complies with N.E.C. Article 547
- Inductive Rating:
  - 16A @ 120V
  - 13.2A @ 208V
  - 12A @ 240V



**Part #E-1612**

Shipping Wt. 2 lb | .9 kg



### Single-Stage Thermostat Features:

- One stage for heating or cooling
- One SPDT staged switch for heating or cooling
- Rugged, weather-resistant enclosure
- Corrosion-resistant materials for long life
- Low mass, high surface area of stainless steel coiled sensor provides rapid response to temperature change
- Temperature Range: 40° to 110° F (4° to 43° C)
- UL Listed, CSA Certified
- NEMA 4X enclosure complies with N.E.C. Article 547
- Inductive Rating:
  - 16A @ 120V
  - 13.2A @ 208V
  - 12A @ 240V